



LESELI DOWNLIGHT CCT

Typology

LED source with SMD technology and high efficiency chip integrated into a recessed luminaire.

Luminaire with facility to select the colour temperature on installation.

Features

Soft satin effect polycarbonate anti-glare diffuser.

Remote power supply equipped with a dip-switch to select the colour temperature.

Flicker Free.

Installation

Complete with springs for easy fastening into false ceilings.


Connection to the mains with terminal block.

Material

Thermally conductive body; extremely light and manageable.

Notes


Providing greater visual comfort, improved definition of detail and reduction of stress.



Characteristic data

Power	22 W	Beam	110°	Dimmable	No	IP	20
Optical compartment IP	43	Flux	2200 lm	PF	0,5	Tc	3000/4000/6000 K
Ra	>80	LED Warranty	G2	Axis	770 cd	RG	RG1

Dimensional characteristics



Ø	216 mm
H	58 mm

Cutting hole	200
--------------	-----

Lighting and photometric features

Beam opening	110°
Flux	2200 lm
CCT nominal colour temperature	3000/4000/6000 K
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B20
Trigger time	<0,2 s
LM80 - Luminous flux maintenance at end of life	70
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	22 W
Dimmable	No
Power factor (PF)	0,5
Number of cycles	100000
Operating temperature	-25°C / +35°C

Photometry

	4000K	H(m)	D(m)	E _{max} (lx)	
	Ra80		112°		
Fixture Power	22W	1	2.95	773	
Source Flux	2200lm	2	5.89	193	
Fixture Flux	2200lm	3	8.84	86	
Efficacy	100lm/W	4	11.79	48	
953133 I _{max} =351cd/klm	I _{max}	773cd	5	14.73	31

EuLumDat file on the site

Other Infotech

Flicker Free	Yes
--------------	-----

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:1997	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-2:2012	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

Logistics data

Item net weight	214 gr
Barcode single item	8011905953133
Number of pieces multiple pack	10
Barcode multiple pack	8011905955373
Minimum order quantity	10