



## LESELI MINI PRO

### Typology

Recessed LED fixtures with integrated drivers.

### Features

Adjustable dichroic effect optics.  
Tilt Adjustability 30°.  
Special design of the lens ensures excellent light beam diffusion.  
Compact and easy to install.  
Flicker Free.

### Installation

Complete with springs for easy fastening into false ceilings.

### Material

Extruded powder coated aluminium body.

### Notes


Providing greater visual comfort, improved definition of detail and reduction of stress.

220-240 Vac	Ra >80		50000 h	IP20 VI IP23 VO	Wire	-25°C +35°C	RG1	A <sup>+</sup>	PRO
		G5h24	FLICKER FREE						

### Characteristic data

Power	8 W	Beam	36°	Dimmable	No	Input	220-240 Vac
Base	Wire	IP	20	Optical compartment IP	23	Flux	680 lm
PF	0,5	Tc	4000 K	Ra	>80	LED Warranty	G5h24
Axis	1820 cd	RG	RG1				

### Dimensional characteristics



ø	85 mm
H	55 mm

Cutting hole	68
--------------	----

## Lighting and photometric features

Beam opening	36°
Flux	680 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
LM80 - Luminous flux maintenance at end of life	70
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	8 W
Input voltage	220-240 Vac
undefined	50 Hz
Dimmable	No
Power factor (PF)	0,5
Weighted energy consumption	8 kWh/1000h
Energy class	A+
Number of cycles	100000
Operating temperature	-25°C / +35°C

## Other Infotech

Flicker Free	Yes
Reflector	Yes

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:1997	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-2:2012	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

## Logistics data

Item net weight	182 gr
Barcode single item	8011905941376
Number of pieces multiple pack	20
Barcode multiple pack	8011905943752
Minimum order quantity	20

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products