



## EVO SLIMFLUX NWB4 BASIC + UGR PANELS

### Typology

Ultra-flat LED fixtures with lateral lighting.

### Features

Side heat dissipation.  
 Immediate switch-on.  
 Colour rendering: Ra>80.  
 Remote power supply included.  
 Do not use with dimmer.  
 If you want to dim or use the multicurrent power supply dimmer.  
 UGR version also available.  
 Class II fittings.

### Installation

Possibilities include: recessed, suspended, ceiling/wall.  
 Surface mounting & adjustable suspension wire kits are available as accessories.

### Material

White painted metal body.

### Use

SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

### Emergency

SLIMFLUX panels can be used with standby emergency kit, code KEMR03.

### Notes


Providing greater visual comfort, improved definition of detail and reduction of stress.

220-240 Vac	Ra >80		25000 h	IP20 VI IP43 VO	Free Wire	-25°C +35°C	RG0	UGR <19	<b>BASIC</b>
	G3								

### Characteristic data

Power	40 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Optical compartment IP	43	Flow	3600 lm	PF	0,95
UGR	<19	Tc	4000 K	Ra	>80	LED Warranty	G3
RG	RG0						

## Dimensional characteristics



L	595 mm
H	10 mm
L2	595 mm

## Lighting and photometric features

Flow	3600 lm
CCT nominal colour temperature	4000 K
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
undefined	50 Hz
Dimmable	No
Power factor (PF)	0,95
Number of cycles	100000
Operating temperature	-25°C / +35°C

## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:1997	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-2:2012	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

## Logistics data

Item net weight	2050 gr
Barcode single item	8011905951276
Number of pieces multiple pack	5
Barcode multiple pack	8011905951801
Minimum order quantity	5