



DECO LED A50 - A60 EVO 330°

Typology

Led lamps with SMD technology and high efficiency chip.

Features

Wide choice of powers and color temperature.

Material

Termoconductive material body; antiglare opal finish of the lamp cover.

Notes


Do not use with dimmers except if otherwise indicated.



Characteristic data

| | | | | | | | |
|-------|--------|------|------|--------------|---------|-------|-------------|
| Power | 10 W | Beam | 330° | Dimmable | Yes | Input | 220-240 Vac |
| Base | E27 | IP | 20 | Flux | 1050 lm | PF | 0,9 |
| Tc | 2700 K | Ra | >80 | LED Warranty | G2 | | |

Dimensional characteristics



| | |
|-------------|--------|
| ø | 60 mm |
| H | 116 mm |
| H Tolerance | ± 3 mm |

Lighting and photometric features

| | |
|---|--------------------|
| Beam opening | 330° |
| Flux | 1050 lm |
| CCT nominal colour temperature | 2700 K |
| Colour of the light | Warm light |
| Colour rendering index | >80 |
| Lifespan | 25000 h |
| LED lifespan | L70B50 |
| Trigger time | <0,2 s |
| Heating time up to 60% of full efficiency | Instant Full Light |
| Mercury | 0 mg |

Electrical characteristics

| | |
|------------------------------------|---------------|
| Rated power | 10 W |
| Input voltage | 220-240 Vac |
| Frequency | 50 Hz |
| Dimmable | Yes |
| Power factor (PF) | 0,9 |
| Input current | 0.048 A |
| Weighted energy consumption | 10 kWh/1000h |
| Energy efficiency class | F |
| Number of cycles | 100000 |
| Operating temperature | -25°C / +35°C |
| Equivalence with incandescent lamp | 75 |

LED Warranty

| | |
|----|--|
| G2 | Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions. |
|----|--|

European Directives

| | |
|--|--|
| 2009/125/EC * Ecodesign 2011/65/EU * RoHS 2012/19/EU * RAEE 2014/30/EU * EMC (Compatibilità Elettromagnetica) 2014/35/EU * LVD (Bassa Tensione) 2015/863 * Amending RoHS 2017/1369 * Regulation for Energy Labelling 2019/2015 * Regulation for Energy Labelling 2019/2020 * Regulation for Ecodesign 2021/340 * Amending Reg. Energy Labelling 2021/341 * Amending Reg. Ecodesign | Product standards CEI EN 55015:2020 (+A11:2020) CEI EN 60968:2016 CEI EN 61000-3-2:2019 (+A1:2021) CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022) CEI EN 61547:2010 CEI EN 62031:2021 (+A11:2022) CEI EN 62471:2010 IEC/TR 62471-2:2009 CEI EN 62560:2013 (+A1:2017/+A11:2020) CEI 34-141:2014 |
|--|--|

Logistics data

| | |
|--------------------------------|---------------|
| Item net weight | 49 gr |
| Barcode single item | 8011905855970 |
| Number of pieces multiple pack | 10 |
| Barcode multiple pack | 8011905855987 |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products