




BISPINA JC - CLEAR

24 Vdc	Ra 100				2000 h	IP20	GY6,35	-15°C +35°C	
--------	--------	--	--	--	--------	------	--------	----------------	--

Characteristic data

Power	50 W	Beam	320°	Dimmable	Yes	Input	24 Vdc
Base	GY6,35	IP	20	Flux	900 lm	Tc	3000 K
Ra	100						

Dimensional characteristics



Ø	12 mm
H	44 mm

Lighting and photometric features

Beam opening	320°
Flux	900 lm
CCT nominal colour temperature	3000 K
Colour rendering index	100
Lifespan	2000 h
LED lifespan	L80
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	50 W
Input voltage	24 Vdc
Dimmable	Yes
Input current	2.08 A
Weighted energy consumption	53 kWh/1000h
Number of cycles	25000
Operating temperature	-15°C / +35°C
Equivalence with incandescent lamp	74
Operating position	360°

Standards and Directives

2006/95/CE * Bassa Tensione	EN 60432-3+A2 * Fascicolo 9673, Anno 2009
2009/125/CE * Progettazione Eco Compatibile	244/2009 * Progettazione Eco Compatibile
2011/65/UE * RoHS	859/2009 * Progettazione Eco Compatibile
EN 60432-3	2010/30/EU * Energy Consumption
EN 60432-3+A1 * Fascicolo 8224, Anno 2006	874/2012 * Regulation for Energy Labelling

Logistics data

Barcode single item	8011905011888
Number of pieces multiple pack	20
Barcode multiple pack	8011905700966